

BLAZEGUARD. FIRE-RATED PANELS **CERTIFIED LOAD LIMITS**

Listed for Uniform Load Capacity by:

Progressive Engineering Inc.

15/32"

BLAZEGUARD.

Roof Sheathing Use

Coated Side AGAINST Framing:

16" o.c. Framing = 200 psf

24" o.c. Framing = 94 psf

- Exceeds snow load requirements THROUGHOUT the state of Minnesota.
- 15/32" Blazeguard Panel stronger than 15/32" plywood.
- Classified as a Class A flame spread structural panel (extended ASTM E-84). Certified in 1-hr and 2-hr fire walls.
- Exceeds 15 minute thermal barrier requirement for foam plastics.
- Shear wall rated.
- 15/32" Blazeguard Panel offers price advantages over competitive products.
- Limited Lifetime Warranty.
- Ecologically friendly; land-fill safe.
- White coated surface highlights certification stamp; ICC identification readily recognizable by code officials.
- Standard APA storage and handling requirements; shipped in reusable lumber bag for on-site storage.
- Standard construction tools and practices apply.
- Formaldehyde-Free and FSC Certified panels available.

(320) 764.5797 *main*
(320) 764.5799 *fax*
(800) 638.4570 *toll free*
USA

510 4th Street North
P.O. Box 379
Watkins, MN 55389

