



GREEN BUILDING

LP® OSB Sheathing can help builders work toward green building certification quickly and easily!

- **LP OSB Sheathing** uses 100% SFI-certified wood from small diameter, rapidly regenerating trees.
- LP uses low-emitting, safe resins as a binder.
- As an engineered product, LP OSB Sheathing uses raw materials more efficiently and offers more consistent performance than other products.

GREEN ATTRIBUTE

Material & Resource Efficiency

- Renewable Materials
- 3rd Party-Certified Wood Products
- Engineered Products

Indoor Air Quality/Health

- Reduced Formaldehyde

WHY LP OSB QUALIFIES

- Wood-Based Product
- SFI-Certified Wood
- Engineered Product
- Minimal Off-Gassing of .03 ppm - at or below background levels

LP products are a natural choice for building green.

As wood-based products they:

- have a low environmental impact
- are a renewable resource

As engineered products they:

- use raw materials more efficiently than traditional products
- are made with low-emitting, safe resins

All of LP's wood-based products are made from third-party certified wood from sustainably managed forests.

GREEN BUILDING PROGRAMS

Selected Green Building Programs where LP® OSB Sheathing Gives Builders Points Toward Certification:

Program	Category	Section	Item	Description	Points
	Resource Efficiency	Renewable Materials	606.1	Two types of biobased products are used	3 to 6
			606.2	Wood or wood-based products are certified to the requirements of one of the following (ATFS, CSA, FSC, PEFC, SFI)	4
			606.3	Materials are manufactured using a minimum of 33% of the primary manufacturing process energy derived from renewable resources, combustible waste sources, or RECs	2
			Resource-Efficient Materials	607.1	Products containing fewer materials are used to achieve the same end-use requirements as conventional products
	Resource Efficiency	Renewable Materials	2.6.1	Use materials manufactured from renewable resources or agricultural byproducts such as soy-based insulation, bamboo, or wood-based products	3
			2.6.2	Use certified wood for wood and wood-based materials and products from all credible third-party certified sources	4
	IAQ/Health	Finishes Reduce Formaldehyde in Interior Finishes (CA Section 01350)	E.8.a	Residences: subfloor	1
	Resource Efficient Building Materials	Advanced Products	226	OSB Roof Decking	1
	Indoor Environmental Quality	Low Emitting Materials - Composite Wood and Agrifiber Materials	IEQ 4.4	Composite wood and agrifiber materials used on the interior of the building shall contain no added urea formaldehyde resins	1

